

ATS Large Digital Displays

- Run Time Accumulators
- Production Monitors
- GPS Clock Systems
- Analog Input Displays
- Counters
- Timers



▲ **AE46S-373**



▲ **AE2412**



▲ **STD-525**



▲ **AE44-503**

BRIGHT RUN TIME ACCUMULATORS

AT/AE24-373	2.3 Inch, Four Digit, MM:SS
AT/AE26-373	2.3 Inch, Six Digit, HH:MM:SS
AT/AE44S-373	4 Inch, Six Digit, MM:SS
AT/AE46S-373	4 Inch, Six Digit, HH:MM:SS

Other sizes and configurations available

ANALOG INPUT DISPLAYS

AT/AE24-341	2.3 Inch, Four Digit, 4-20 mA
AT/AE2412-341	2.3 & 1 Inch, Six Digit, 0-5VDC
AT/AE26-341	2.3 Inch, Six Digit, 0-10VDC
AT/AE24F-341	2.3 Inch, Four Digit, Flush Mount
AT/AE2412F-341	2.3 & 1 Inch, Six Digit, Flush Mt.
AT/AE42S-341	4 Inch, Two Digit, 4-20mA
AT/AE43S-341	4 Inch, Three Digit, 0-5VDC
AT/AE44S-341	4 Inch, Four Digit, 0-10VDC
AT/AE45S-341	4 Inch, Five Digit, 4-20mA
AT/AE46S-341	4 Inch, Six Digit, 0-10VDC

Four Digit Resolution

PRECISION TIMERS

AT/STD-11-2	Measure & Display Accurate Elapsed Time: 0.000 - 9999.999 Seconds
AT/STD-525T	Measure Accurate Elapsed Time Minutes, Seconds, Tenths and Hundredths of seconds
AT/2171-2	Handheld Pendant Control

POWER OPTIONS

12VAC	12 VAC, 60HZ
12V3	12 VDC to 15 VDC
24VAC	24 VAC, 60 Hz, 5VA
220V1	220 VAC, 60 Hz, 12.6 VA
PC8	Add 120 VAC Power Cord, 8' long

ENCLOSURE OPTIONS

OPT-N12A	NEMA 12 rated, 16"W x 8"H x 6"D
OPT-N12B	NEMA 12 rated, 24"W x 8"H x 6"D
OPT-N4XA	NEMA 4X rated Stainless Steel, 16"W x 8"H x 6"D
OPT-N4XB	NEMA 4X rated Stainless Steel, 24"W x 8"H x 6"D

NEMA enclosures available on selected models

Large Bright Red LED Displays with digit sizes from 1" to 12" high. Visible from 25 feet to 500 feet. Display temperature, pressure, flow and other process variables. Accumulate machine cycle time, run time or downtime. Monitor production counts. Synchronized clock systems with GPS accuracy. Count-up or countdown elapsed time. Custom units available.

SYNCHRONIZED CLOCK SYSTEMS

AT/MC4181LV	Master Clock to synchronize Clocks, Bells, Time & Attendance System with Computer
AT/GPS-TR3	GPS Master Clock Interface, includes Antenna/Receiver and Interface.
AT/CC2002	Four digit, four inch red LED Clock Single sided, wall mount, 24 VAC
AT/CC2002W2	Four digit, four inch red LED Clock Double sided, wall mount, 24 VAC
AT/CC2002C2	Four digit, four inch red LED Clock Double sided, ceiling mt, 24 VAC
AT/CC2002F	Four digit, four inch red LED Clock Single sided, flush mount, 24 VAC
AT/8901-1821	24VAC, 200VA, (8 Amp) Power Supply. 12" x 12" x 4"

COUNTER OPTION

OPT-230	Event Counter (To 25Hz Speed)
Input signals:	12-120V AC or DC, >20ms duration

PRODUCTION MONITORS

AT/AE44-503J	Monitor GOAL and ACTUAL counts Two lines of four digits, four inch
AT/AE44-503C	Designed for use with Remote Controller.
AT/AE-503DX1	Controller for AE44-503C above

DIGIT SIZE	VIEWING DISTANCE	
	Typical	Maximum
2.3"	70 ft	110 ft
4"	120 ft	200 ft
8"	240 ft	400 ft
12"	360 ft	600 ft

Misc.